

Technical Data Sheet : 229

Validity date : 02nd May 2007

➤ Product Description :	BOPP adhesive tape	
	Acrylic adhesive	
	Noisy unwinding	
	Excellent initial tack	
	‘Ecological’ solvent-free tape	
➤ Technical Data :	Backing thickness :	28 my ± 3 %
	Total thickness :	47 my ± 6 %
	Adhesion to steel:	≥ 230 g/cm
	Tensile strength :	≥ 4,6 kg /cm
	Elongation at break :	≤ 165 %
➤ Application :	Recommended for medium duty boxes with hand dispenser Recommended for automatic carton sealing machines	
➤ Warning :	Protect from humidity – Use and store at temperature above 18°C.	
➤ Abovementioned technical data are valid also for the following versions:	C = coloured J = jumbo P = pre-printed ET = easy tear	
➤ Data referring to tensile strength and elongation at break cannot be applied to ET version = easy tear		

Test methods : AFERA - PSTC. rev. 1 Fabo

Abovementioned values represent the average values of our regular production; as such, they are not binding. Customer must verify through practical tests that product is fit for the use he intends it for and is responsible for any risk and damage caused by the use of the product. Abovementioned values may be changed at any moment for production needs or technical updates

FABO SPA Via Cecinese 84 51036 Larciano (PT) Tel 0573 84851 Fax 0573 84109