



DONGGUAN HING SHING ADHESIVE PRODUCT CO.,LTD
BAOLIAN INDUSTRIAL PARK, GAOBU, DONGGUAN, CHINA
TEL: +86 769 81300836 FAX: 81300830 MAIL: INFO@HYSEAL.COM

TECHNICAL DATA SHEET

Description:	Polypropylene Packaging Tape Noisy 48mm x 132m	
Color:	Transparent	
Backing Material :	Bi-axially Oriented Polypropylene	
Adhesive :	Emulsion Pressure Sensitive Water Based Acrylic	
Film Thickness:	23 mu	(ASTMD 3652)
Coating Weight:	20 gr/m2	(ASTMD 3652)
	(Note: +/-6% on coating thickness is acceptable)	
Adhesive Solid Content	55%	(BA)
Initial Tack:	3.5 cm	(ASTMD-3121M)
Peeling Adhesion:	12.85 N/inch	(ASTMD-3330M)
Shear Value on Steel:	> 24 hours	(ASTMD-3654M)
Tensile Strength:	130.0 N/inch	(ASTMD-3759)
Elongation at break:	145%	(ASTMD-3759)
Application Temperature:	(15C+ --65C+)	

STORAGE

- * Use at a temperature of 18C degrees.
- * For a better application, do not store more than 6 months and keep the product in original packaging at 22C+ and 50% humidity.
- * The product should be protected from extreme temperature, humidity and direct sun lights.
- * Once removed from its original packaging the tapes should be protected properly.

IMPORTANT

The adhesive properties are susceptible to change depending on several parameters such as the composition and condition of the substrate impurities in or on the substrate temperature and humidity of the storage and envirenmental conditions during the application. Etc.

The above mentioned information is average values as the result of production samples and are not a guarantee of a final result.

Before using the product the customer should carry out its own tests in order to determine the product suitability for its specific application in real operative conditions and according to its own requirements.